


Advanced CMOS Logic Delay Module

The Advanced CMOS Logic Delay Modules manufactured by Engineered Components Company are designed to provide output waveforms that reproduce the input waveform after a set amount of delay time has elapsed. The five output waveforms are delay line taps provided at 20% increments of the total delay (20, 40, 60, 80, and 100%). These delay modules are non-inverting. The delay times are calibrated to the listed tolerances on the rising edge delays. The products with a total delay of less than 30ns have additional delay present at tap 1 due to internal propagation delays (see the Product Selection Table).


The MTBF on these modules, when calculated per MIL-HDBK-217, for a 50 deg.C ground fixed environment and with 50VDC applied, is in excess of 1.3 million hours. The temperature coefficient of delay is less than 500 ppm/deg.C over the operating temperature range of -40 to +85 deg. C.

The module is provided in a 16-pin DIP package, fully encapsulated in epoxy resin and is housed in a Diallyl Phthalate case, blue in color. The case marking is applied by silkscreen using white epoxy paint. The 11 copper leads are tin-lead plated and meet the solderability requirements of MIL-STD-202, Method 208.

BLOCK DIAGRAM



MECHANICAL DIAGRAM



Product Selection Table

Part Number	Output Delay and Tolerances (in ns)				
	Tap 1 (20%)	Tap 2 (40%)	Tap 3 (60%)	Tap 4 (80%)	Tap 5 (100%)
LDM-ACT-10	6.0+/-1.0	7.0+/-1.0	8.0+/-1.0	9.0+/-1.0	10.0+/-1.0
LDM-ACT-14	6.0+/-1.0	8.0+/-1.0	10.0+/-1.0	12.0+/-1.0	14.0+/-1.0
LDM-ACT-18	6.0+/-1.0	9.0+/-1.0	12.0+/-1.0	15.0+/-1.0	18.0+/-1.0
LDM-ACT-22	6.0+/-1.0	10.0+/-1.0	14.0+/-1.0	18.0+/-1.0	22.0+/-1.0
LDM-ACT-26	6.0+/-1.0	11.0+/-1.0	16.0+/-1.0	21.0+/-1.0	26.0+/-1.0
LDM-ACT-30	6.0+/-1.0	12.0+/-1.0	18.0+/-1.0	24.0+/-1.0	30.0+/-1.5
LDM-ACT-35	7.0+/-1.0	14.0+/-1.0	21.0+/-1.0	28.0+/-1.5	35.0+/-1.5
LDM-ACT-40	8.0+/-1.0	16.0+/-1.0	24.0+/-1.0	32.0+/-1.5	40.0+/-2.0
LDM-ACT-45	9.0+/-1.0	18.0+/-1.0	27.0+/-1.5	36.0+/-1.5	45.0+/-2.0
LDM-ACT-50	10.0+/-1.0	20.0+/-1.0	30.0+/-1.5	40.0+/-2.0	50.0+/-2.0
LDM-ACT-55	11.0+/-1.0	22.0+/-1.0	33.0+/-1.5	44.0+/-2.0	55.0+/-2.0
LDM-ACT-60	12.0+/-1.0	24.0+/-1.0	36.0+/-1.5	48.0+/-2.0	60.0+/-2.0
LDM-ACT-65	13.0+/-1.0	26.0+/-1.5	39.0+/-1.5	52.0+/-2.0	65.0+/-2.5
LDM-ACT-70	14.0+/-1.0	28.0+/-1.5	42.0+/-2.0	56.0+/-2.0	70.0+/-2.5
LDM-ACT-75	15.0+/-1.0	30.0+/-1.5	45.0+/-2.0	60.0+/-2.0	75.0+/-2.5
LDM-ACT-80	16.0+/-1.0	32.0+/-1.5	48.0+/-2.0	64.0+/-2.5	80.0+/-3.0
LDM-ACT-85	17.0+/-1.0	34.0+/-1.5	51.0+/-2.0	68.0+/-2.5	85.0+/-3.0
LDM-ACT-90	18.0+/-1.0	36.0+/-1.5	54.0+/-2.0	72.0+/-2.5	90.0+/-3.0
LDM-ACT-95	19.0+/-1.0	38.0+/-1.5	57.0+/-2.0	76.0+/-2.5	95.0+/-3.0
LDM-ACT-100	20.0+/-1.0	40.0+/-1.5	60.0+/-2.0	80.0+/-3.0	100.0+/-3.0
LDM-ACT-125	25.0+/-1.0	50.0+/-2.0	75.0+/-2.5	100.0+/-3.0	125.0+/-4.0
LDM-ACT-150	30.0+/-1.5	60.0+/-2.0	90.0+/-3.0	120.0+/-4.0	150.0+/-5.0
LDM-ACT-175	35.0+/-1.5	70.0+/-2.5	105.0+/-4.0	140.0+/-4.5	175.0+/-5.0
LDM-ACT-200	40.0+/-1.5	80.0+/-3.0	120.0+/-4.0	160.0+/-5.0	200.0+/-6.0
LDM-ACT-225	45.0+/-2.0	90.0+/-3.0	135.0+/-4.0	180.0+/-6.0	225.0+/-7.0
LDM-ACT-250	50.0+/-2.0	100.0+/-3.0	150.0+/-5.0	200.0+/-6.0	250.0+/-8.0

Special modules can often be manufactured to provide for customer specific applications.

Operating Specifications:

All measurements made at 25 deg. C
 All measurements made with Vcc = +5VDC
 All measurements made with (1) ACT output load

Operating Temperature: -40 to +85 deg. C
 Storage Temperature: -55 to +125 deg. C

Vcc Supply Voltage: 4.75 to 5.25VDC
 Vcc Supply Current:
 Constant "0" or "1" in = 1nA typical
 Constant 1 MHz square wave in = 4mA typical

Logic "High" Input:
 Voltage: 2.0VDC min. ; Vcc max.
 Logic "Low" Input:
 Voltage: 0.8 VDC max.
 Logic "High" Voltage Out: 4.3VDC min. @ -24mA
 Logic "Low" Voltage Out: 0.44VDC max. @ +24mA



engineered components company

A Division of Cornucopia Tool & Plastics, Inc. PO Box 1915, 448 Sherwood Rd., Paso Robles CA 93447

Phone: 805-369-0034

Fax: 805-369-0033

Web: www.ec2.com