


8-Bit Programmable TTL Logic Delay Line

The 8-Bit Programmable TTL Logic Delay Lines manufactured by Engineered Components Company are designed to provide output waveforms that reproduce the input waveform after a set amount of delay time has elapsed. The final delay of the output waveform can be adjusted during or after installation into a circuit. The adjustment is made by applying a logic "0" or "1" at each of the 8 multiplexor programming pins (see the Truth Table Examples). The delay times are calibrated to the listed tolerances on the rising edge delays (see the Product Selection Table).


The MTBF on these modules, when calculated per MIL-HDBK-217, for a 50 deg.C ground fixed environment and with 50VDC applied, is in excess of 0.30 million hours. The temperature coefficient of delay is less than 150 ppm/deg.C over the operating temperature range of 0 to +70 deg. C.

The module is provided in a 64-pin DIP package, fully encapsulated in epoxy resin and is housed in a Diallyl Phthalate case, blue in color. The case marking is applied by silkscreen using white epoxy paint. The 18 copper leads are tin-lead plated and meet the solderability requirements of MIL-STD-202, Method 208.

BLOCK DIAGRAM



MECHANICAL DIAGRAM



Product Selection Table

Part Number	Output Delays and Tolerances (in ns)			
	*Step Zero Delay	Maximum Delay (Nominal)	Delay Change Per Step	** Maximum Deviation From Programmed Delay
PTTLDL-20-1	20.0+/-0.5	275	1.0	+/-6.0
PTTLDL-20-2	20.0+/-0.5	530	2.0	+/-8.0
PTTLDL-20-3	20.0+/-0.5	785	3.0	+/-12.0
PTTLDL-20-4	20.0+/-0.5	1040	4.0	+/-16.0
PTTLDL-20-5	20.0+/-0.5	1295	5.0	+/-20.0

* Delay at step zero is referenced to the input pin.

**All delay times after step zero are referenced to step zero.

TRUTH TABLE EXAMPLES (Delay times in ns)

Part Number	Programming Pin 8	Programming Pin 7	Programming Pin 6	Programming Pin 5	Programming Pin 4	Programming Pin 3	Programming Pin 2	Programming Pin 1		
PTTLDL-20-1	0	0	0	0	0	0	0	0	0	0	0	1	1	
PTTLDL-20-2	0	0	0	0	0	0	0	0	0	0	0	1	1	
PTTLDL-20-3	0	0	0	0	0	0	0	0	0	0	0	1	1	
PTTLDL-20-4	0	0	0	0	0	0	0	0	0	0	0	1	1	
PTTLDL-20-5	0	0	0	0	0	0	0	0	0	0	0	1	1	
PTTLDL-20-1	20	1	2	3	4	5	6	7	8	9	10	11	254	255
PTTLDL-20-2	20	2	4	6	8	10	12	14	16	18	20	22	508	510
PTTLDL-20-3	20	3	6	9	12	15	18	21	24	27	30	33	762	765
PTTLDL-20-4	20	4	8	12	16	20	24	28	32	36	40	44	1016	1020
PTTLDL-20-5	20	5	10	15	20	25	30	35	40	45	50	55	1270	1275

Special modules can often be manufactured to provide for customer specific applications.

Operating Specifications:

All measurements made at 25 deg. C
 All measurements made with Vcc = +5VDC
 All measurements made with (1) TTL output load

Operating Temperature: 0 to +70 deg. C
 Storage Temperature: -55 to +125 deg. C

Vcc Supply Voltage: 4.75 to 5.25VDC

Vcc Supply Current = 185mA typical

Logic "High" Input:

Voltage: 2.0VDC min. ; Vcc max.

Current: 2.7VDC = 100uA max. ; 5.5VDC = 1mA max.

Logic "Low" Input:

Voltage: 0.8 VDC max.

Current: -4mA max.

Logic "High" Voltage Out: 2.7VDC min.

Logic "Low" Voltage Out: 0.5VDC max.

Multiplexor setup time = 4ns typ.



engineered components company

A Division of Cornucopia Tool & Plastics, Inc. PO Box 1915, 448 Sherwood Rd., Paso Robles CA 93447

Phone: 805-369-0034

Fax: 805-369-0033

Web: www.ec2.com